

1. Take the leg frame with the handlebar (Part A), and lay it flat on the ground.
  2. Determine which direction you would like the seat to face in your bathtub. The leg frame with the handlebar (Part A) will be the side that goes inside the bathtub.
  3. There are two sliding rails (Part C): one rail has 2 brass push buttons, and the other rail has 4 push buttons.
  4. Take the rail with 4 push buttons, and insert it into the side of the frame you want the seat to face, making sure the two larger push buttons face down, and the two smaller push buttons face outwards (the smaller push buttons are for the sliding rail locking mechanisms). Make sure the larger, bottom button snaps firmly into the frame.
  5. Insert the other sliding rail into the other side of the leg frame (Part A), making sure the button snaps firmly into place.
- 
6. Take the seat with the attached sliding rings (Part D), and align the sliding rings with the rails, so that the locking side of the seat (the side with the red tabs) is on the same rail as the 4 brass push buttons. Insert both sliding rails into the sliding rings under the seat. Push in the push buttons to slide seat easily onto the rails.
- 
7. Take the other leg frame (Part B), and insert the sliding rails into it. Make sure the brass buttons snap firmly into place.
- 
8. Take the 4 legs (Part E), and insert them into the leg frames. Set the bench height by using the same button-hole location for each leg. Make sure the buttons snap firmly into place. For your safety, adjust the rubber tips on the legs by turning them outward for maximum floor contact.
- 
9. Sit the bench up on the legs. Take the backrest (Part F), and press the two brass push buttons on the frame of the backrest. Insert the backrest into the tubes underneath the seat, and push it in until the brass push buttons snap firmly into place.
-

## Tips for Care and Use


### Safety Belt

For added security and stability, adjust the safety belt around the user's lap.


### Locking Mechanism

Lock the seat into place by making sure the slide ring snaps firmly onto the brass push button at the end of the sliding rail (shown below). Release the locking mechanism by pressing down on the red tab of the locked slide ring.

**UNLOCKED**



**LOCKED**



### Sliding Rails

If the seat is not sliding as smooth as you would like, we recommend spraying WD40 along the sliding rails.

### Rubber Tips

Be sure the rubber tips are turned outward for maximum floor contact and stability.

### Cleaning

Rinse off the seat area with water after each use to prevent dirt, soap scum, and mineral deposits from forming which could block the push button areas.

If any push button does not completely snap into place, or if you feel the bench is not secure, please do not use the bench, and notify your authorized dealer immediately.

*Have Questions? Please contact your authorized dealer for assistance.*

Thank you for purchasing an Eagle Health Supplies product!

*If you would like to register your product for the 1-year warranty, please fill out the included Warranty Card, and return to Eagle Health Supplies.*



**EAGLE HEALTH SUPPLIES INC.**  
[www.eaglehealth.com](http://www.eaglehealth.com)

## Instruction Pamphlet

**For Snap-N-Save Sliding Transfer Benches**

**77111, 77181, 77191  
77211, 77281, 77291  
77311, 77381, 77391**

Email: [sales@eaglehealth.com](mailto:sales@eaglehealth.com)  
Phone: (714) 532 - 1777  
Fax: (714) 532 - 9777